



US009636964B2

(12) **United States Patent**
Kuriki

(10) **Patent No.:** **US 9,636,964 B2**

(45) **Date of Patent:** **May 2, 2017**

(54) **DAMPER**

(71) Applicant: **HONDA MOTOR CO., LTD.**, Tokyo (JP)

(72) Inventor: **Nobuharu Kuriki**, Wako (JP)

(73) Assignee: **HONDA MOTOR CO., LTD.**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/835,995**

(22) Filed: **Aug. 26, 2015**

(65) **Prior Publication Data**

US 2016/0059658 A1 Mar. 3, 2016

(30) **Foreign Application Priority Data**

Aug. 28, 2014 (JP) 2014-174116

(51) **Int. Cl.**
B60G 13/14 (2006.01)

(52) **U.S. Cl.**
CPC **B60G 13/14** (2013.01); **B60G 2202/24** (2013.01); **B60G 2202/416** (2013.01); **B60G 2204/62** (2013.01); **B60G 2206/41** (2013.01); **B60G 2300/60** (2013.01); **B60G 2400/91** (2013.01); **B60G 2500/10** (2013.01); **B60G 2600/188** (2013.01); **B60G 2600/21** (2013.01); **B60G 2800/162** (2013.01)

(58) **Field of Classification Search**

CPC B60G 13/14

USPC 290/1 R

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,295,538 A * 10/1981 Lewus B60G 13/14 180/165
5,337,560 A * 8/1994 Abdelmalek B60G 13/14 180/65.25
5,570,286 A * 10/1996 Margolis B60G 13/14 180/165
2004/0150361 A1 * 8/2004 Hio B60G 17/0165 318/375
2007/0089924 A1 * 4/2007 de la Torre B60G 13/14 180/305
2008/0257626 A1 * 10/2008 Carabelli B60G 13/14 180/165

(Continued)

FOREIGN PATENT DOCUMENTS

JP 2004-237824 A 8/2004
JP 2007-233985 A 9/2007

(Continued)

OTHER PUBLICATIONS

Japanese Office Action dated Jan. 12, 2016 (mailing dated), issued in related Japanese Patent Application No. 2014-174116.

Primary Examiner — Tulsidas C Patel

Assistant Examiner — Charles Reid, Jr.

(74) *Attorney, Agent, or Firm* — Westerman, Hattori, Daniels & Adrian, LLP

(57) **ABSTRACT**

A damper includes a polarized capacitor electrically connected to an electromagnetic motor. The surface area at a first fluid chamber side of a piston head is different from the surface area at a second fluid chamber side of the piston head in a cylinder. A positive electrode side of the polarized capacitor is connected to the electromagnetic motor at a side at which output voltage from the electromagnetic motor is positive when the piston head is displaced toward the first fluid chamber side.

4 Claims, 9 Drawing Sheets

